





What's a Standby Generator?	5
Generators 101: How It Works	
Standby Generator vs. Portable Generator	8
Why KOHLER _® Generators?	
The Power Inside – What You Need to Know	
Estimate Your Power Needs.	14
Find Your Perfect Generator	
10 kW/12 kW	17
12 kW	18
14 kW/20 kW	. 19-20
24 kW/30 kW	21
38 kW/48 kW	
60 kW	
80 kW/100 kW	24
125 kW/150 kW	
KOHLER Generators Trusted Worldwide for Nearly a Century	



WHAT'S A STANDBY GENERATOR?

A KOHLER_® standby generator is installed outside your home or business like an AC unit. It's wired into the electrical panel and comes on automatically during a power outage. KOHLER generators run on propane or natural gas, so there's no refueling needed.

In just 10 seconds, a KOHLER generator automatically powers your AC, heat, sump pump and major appliances like your fridge and oven.* If you own a business, we're talking HVAC, lights, security system, cash register and computer.* Everything, all at the same time. And you don't have to do a thing.

^{*}Based on generator and load size.









1. Before the power goes out

Your automatic transfer switch (ATS) monitors the electricity coming from the utility. It's working 24/7 to protect your home.

2. The power goes out

When the power fails or drops below an acceptable level (brownout), the ATS signals the generator to start. In seconds, the ATS transfers your power from the utility to the generator.

3. Your generator powers your home

The generator supplies your home or business with electricity until the utility power is restored.

4. The utility power returns

When the utility power is restored, the ATS automatically transfers your power source from the generator to the utility.

5. Your generator turns off

Your KOHLER_® generator automatically shuts down, ready for the next power outage.

STANDBY GENERATOR VS. PORTABLE GENERATOR

When it comes to backup power, you have two choices.

Standby Generators

- Ideal for backing up your home or business
- Powers critical hardwired systems like AC, heat, sump pump, well pump, security system and large appliances
- Automatically starts and restores power in seconds, whether you're there or not
- No refueling—runs on your building's natural or LP gas
- Delivers high-quality power won't harm your electronics



Portable Generators

- Designed for job sites, camping, tailgating and limited backup power
- Powers plug-in items through extension cords or hardwired items through optional manual transfer switch
- Runs on gasoline, natural gas or liquid propane gas
- Operates outdoors using careful safety guidelines





Total Reliability

During our design process, every KOHLER® generator endures hundreds of performance tests to ensure total reliability. That's why homes, businesses, governments, even the National Weather Service trust dependable, long-lasting KOHLER generators.

Powers Everything

In just 10 seconds, KOHLER generators can automatically power your HVAC, sump pump and major appliances—all at the same time.*

High-Quality Power

Our high-quality power output protects your sensitive electronics from erratic power surges.

Outlasts the Outage

Every KOHLER generator features a heavy-duty engine built to exceed the demands of standby power.

Long warranty

You get our five-year, 2,000-hour limited warranty, plus a corrosion-proof enclosure that's built to last.[†]

^{*}Based on generator and load size.

^{†14}RESA(L) and 20RESC(L) models feature corrosion-proof enclosure; all other models feature corrosion-resistant enclosures.

THE POWER INSIDE—WHAT YOU NEED TO KNOW

The Engine in Your Kohler Generator

The engine is the heart of generator performance and reliability—and a key indicator of generator quality.

Inside every KOHLER generator is a heavy-duty engine built to withstand extreme workloads over many years. These engines are tested and proven in punishing environments, such as industrial construction, that far exceed the demands of standby power. They produce significant power while staying true to voltage and frequency ratings.



Why Motor Starting Is Important

Generator wattage isn't the only criteria for buying a home generator – peak motor starting is important too. That's because large appliances like your AC and fridge need sharp increases in power to start up.

KOHLER generators handle those peak load demands with high motor-starting ratings that won't drop power to other appliances. In fact, depending on your electrical requirements, you may find that a smaller generator with a high starting rating will work for you.





ESTIMATE YOUR POWER NEEDS

Here's a quick tool to "ballpark" the right size KOHLER® generator for your home or business. The best way to determine your specific power needs is to ask your generator professional to perform a site survey. He or she will analyze your electrical load and specify and install the proper generator system.



YOUR ELECTRICAL NEEDS	10–14 kW	15-25 kW	26-48 kW	49-150 kW
Furnace fan	х	х	х	
Refrigerator/freezer	х	Х	Х	
Sump pump	Х	Х	Х	
Lighting	х	Х	Х	
Well pump	Х	Х	Х	
Television/radio	х	Х	Х	
Computer	Х	Х	Х	
Garage door opener	х	Х	Х	For greater than
Security system	Х	Х	Х	200-amp service
Central air system	х	Х	Х	in larger homes and small
Water heater		Х	Х	businesses
Washing machine		Х	Х	
Electric range		Х	Х	
Clothes dryer			Х	
Dishwasher			Х	
Microwave oven			Х	
Toaster oven			Х	
Extensive power requirements			Х	

This chart provides a rough sizing estimate. As always, the best way to determine your specific power needs is to consult a licensed electrical contractor. Visit KohlerGenerators.com for a sizing calculator to determine your needs.



MODEL	10RESV	12RESV
Rated Power Lpg (Liquid Propane)/Ng (Natural Gas) (Kw)	10/9	12/11
Voltage @ 60 Hz Single-Phase	120/	240
Amps Lpg/Ng @ 240 V Single-Phase	41.7/37.5	50/45.8
Engine/Alternator Rpm	36	00
Three-Phase Available	N	0
	725	
	21.4	
Engine	KOHLER	
	7000 Series OHV KT725	
	V-Twi	
Peak Motor Starting kVA at 240 V	16.8 kVA	
Fuel	LPG/NG	
Engine Cooling	Air-Cooled	
Enclosure	Steel	
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	64/69	
Dimensions (L x W x H) in.	28 x 30 x 32	
Digital Voltage Regulation	+/- 1.0%	
Warranty	5-Year Limited	



10 kW



12 kW (12RESV)

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating, Ratings are in accordance with ISO-304671, RSS514, ASS799 and DIN 8271.

"Single-point sound levels are the lowest of 8 point measured around the generator. 14RCA and 20RCA sound levels are measured at the front of the generator. Actual sound levels may vary based on installation parameters.

MODEL	12RES
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	12/10.4
Voltage @ 60 Hz Single-Phase	120/240
Amps LPG/NG @ 240 V Single-Phase	50/43
Engine/Alternator rpm	3600
Three-Phase Available	No
	721 cc
	23.6 hp
	KOHLER
Engine	Command PRO OHV CH740
	V-Twin
	Hydraulic
Pools Motor Ctarting Is/A at 240 V	Valve Lifters 32 kVA
Peak Motor Starting kVA at 240 V Fuel	LPG/NG
	Air-Cooled
Engine Cooling Enclosure	Steel
Single-Point Sound Output dBA at 23 ft.	Steel
(during exercise/normal operation)*	63
Dimensions (L x W x H) in.	44 x 29 x 32
Digital Voltage Regulation	+/-1.5%
Response Time	10 Seconds
Warranty	5-Year Limited [†]



12 kW (12RES)

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-306/f. ISS5514, AS2799 and DN 627.

[&]quot;Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation. "Non-standby warranty of 18 months or 1000 hours available on 12RES, 14RCA and 14RESA.

MODEL	14RCA	20RCA	
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	14/12	20/18	
Voltage @ 60 Hz Single-Phase	120/	120/240	
Amps LPG/NG @ 240 V Single-Phase	58/50	83/75	
Engine/Alternator rpm	360	00	
Three-Phase Available	Ye	es .	
Engine	725 cc 23.6 hp KOHLER Command PRO OHV CH740 V-Ti Hydraulic V.		
Peak Motor Starting kVA at 240 V	33 kVA	41 kVA	
Fuel	LPG/NG		
Engine Cooling	Air-Cooled		
Enclosure	Corrosion-Resis	stant Aluminum	
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)†	62/67	64/69	
Dimensions (L x W x H) in.	47 x 26 x 32		
Digital Voltage Regulation	+/- 1.0%		
Response Time	10 Seconds		
Warranty	5-Year Limited‡		





20 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-300401, BSS514, ASS298 and DIN 8271.

*8-point logarithmic average, †Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation. ‡Non-standby warranty of 18 months or 1000 hours available on 12RES 14RESA and 14RCA.

MODEL	14RESA	20RESC
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	14/12	20/18
Voltage @ 60 Hz Single-Phase	120/240	
Amps LPG/NG @ 240 V Single-Phase	58/50	83/75
Engine/Alternator rpm	360	00
Three-Phase Available	Ye	s s
	725 cc	999 cc
	23.6 hp	30.9 hp
	KOHLER	KOHLER
Engine	Command PRO	Command PRO
	OHV CH740	OHV CH1000
	V-Twin	
	Hydraulic Valve Lifters	
Peak Motor Starting kVA at 240 V	33 kVA	41 kVA
Fuel	LPG/NG	
Engine Cooling	Air-Cooled	
Enclosure	100% Corrosion-Proof Composite	
Single-Point Sound Output dBA at 23 ft.	58/63	62/67
(during exercise/normal operation)*	36/63	02/07
Dimensions (L x W x H) in.	48 x 26 x 29	
Digital Voltage Regulation	+/- 1.0%	
Response Time	10 Seconds	
Warranty	5-Year Limited [†]	





20 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-306/1. ISS5514, ASZP9 and DIN 627.

*Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation. Non-standby warranty of 18 months or 1000 hours available on 12RES, 14RCA and 14ESA.

MODEL	24RCL	30RCL
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	24/21	30/30
Voltage @ 60 Hz Single-Phase	120/240	
Amps LPG/NG @ 240 V Single-Phase	100/87	125/125
Engine/Alternator rpm	18	00
Three-Phase Available	Ye	es
	2.2 L	2.2 L Turbo
	39 hp	64 hp
Engine	KOHLER KG2204 Naturally Aspirated	KOHLER KG2204T Turbo
	In-Line 4	
	Hydraulic Valve Lifters	
Peak Motor Starting kVA at 240 V	37 kVA	44 kVA
Fuel	LPG/NG	
Engine Cooling	Liquid-Cooled	
Enclosure	Corrosion-Resistant Aluminum	
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	53/60	54/61
Dimensions (L x W x H) in.	74 x 33 x 45	
Digital Voltage Regulation	+/- 1.0%	
Response Time	10 Seconds	
Warranty	5-Year Limited	





30 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-304671, BSS514, ASS298 and DIN 6271.

[&]quot;Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation.

MODEL	38RCLB	48RCLB
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	38/38	48/48
Voltage @ 60 Hz Single-Phase	120/240	
Amps LPG/NG @ 240 V Single-Phase	158/158	200/200
Engine/Alternator rpm	18	00
Three-Phase Available	Ye	es
	2.2 L Turbo	6.2 L
	75 hp	103 hp
Engine	KOHLER KG2204T Turbo	KOHLER KG6208 6.2L NA
	In-Line 4	V-8
	Hydraulic Valve Lifters	
Peak Motor Starting kVA at 240 V	74 kVA	113 kVA
Fuel	LPG	i/NG
Engine Cooling	Liquid-	Cooled
Enclosure	Corrosion-Resi	stant Aluminum
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	54/61	57/61
Dimensions (L x W x H) in.	74 x 33 x 45	90 x 33 x 47
Digital Voltage Regulation	+/- 1.0%	
Response Time	10 Seconds	
Warranty	5-Year Limited	



38 kW



48 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-304671, BSS514, ASSF98 and DN 8271.

*Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation.

MODEL	60RCLA
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	60/58
Voltage @ 60 Hz Single-Phase	120/240
Amps LPG/NG @ 240 V Single-Phase	250/242
Engine/Alternator rpm	1800
Three-Phase Available	Yes
	6.2 L
	103 hp
Engine	KOHLER KG6208 6.2L
	NA Hydraulic Valve Lifters
Dook Motor Starting kVA at 240 V	144 kVA
Peak Motor Starting kVA at 240 V	
Fuel	LPG/NG
Engine Cooling	Liquid-Cooled
Enclosure	Corrosion-Resistant Aluminum
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	57/61
Dimensions (L x W x H) in.	90 x 33 x 47
Digital Voltage Regulation	+/- 1%
Response Time	10 Seconds
Warranty	5-Year Limited



RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-304671, BSS514, ASSF98 and DN 8271.

*Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation.

MODEL	KG80R	KG100R	
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	80/80	100/100	
Voltage @ 60 Hz Single-Phase	12	120/240	
Amps LPG/NG @ 240 V Single-Phase	334/334	417/417	
Engine/Alternator rpm	1	800	
Three-Phase Available		Yes	
	6.2	L Turbo	
	133 hp	173 hp	
Engine	KOHLER	KOHLER KG6208 TA	
	Turbocharged	Turbocharged / Aftercooled V-8	
	Hydraulic	Valve Lifters	
Peak Motor Starting kVA at 240 V	237 kVA	440 kVA	
Fuel	LP	LPG/NG	
Engine Cooling	Liquio	d-Cooled	
Enclosure	Steel (Aluminu	ım Also Available)	
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	6	64/69	
Dimensions (L x W x H) in.	138 x 5	138 x 52.8 x 76.7	
Digital Voltage Regulation	+/-	+/- 0.5%	
Response Time	10 S	10 Seconds	
Warranty	5-Yea	5-Year Limited [†]	





100 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-30467, ISSS14, ASS789 and DN 827.

*Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation. '5-year warranty is an included option for quick ship 80- to 150-kW models.

MODEL	KG125R	150ERESC	
Rated Power LPG (Liquid Propane)/NG (Natural Gas) (kW)	105/125	134/144	
Voltage @ 60 Hz Single-Phase	120	0/240	
Amps LPG/NG @ 240 V Single-Phase	438/521	567/600	
Engine/Alternator rpm	1	800	
Three-Phase Available	`	Yes	
	6.2 L Turbo	8.8 L Turbo	
	201 hp	259 hp	
Engine	KOHLER KG10V08T Turbocharged	General Motors Vortec V-8	
	Hydraulic Valve Lifters		
Peak Motor Starting kVA at 240 V	440 kVA		
Fuel	LPG/NG		
Engine Cooling	Liquid	l-Cooled	
Enclosure	Steel (Aluminu	m Also Available)	
Single-Point Sound Output dBA at 23 ft. (during exercise/normal operation)*	64/69	NA/72	
Dimensions (L x W x H) in.	138 x 52.8 x 76.7	139 x 45 x 66	
Digital Voltage Regulation	+/-	+/- 0.5%	
Response Time	10 Seconds		
Warranty	5-Year	5-Year Limited [†]	





150 kW

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-3046(1), ISSS14, ASS798 and DIN 62798 and DIN 6279.

[&]quot;Single-point sound levels are compared to competitive ratings. Lowest of 8 points measured around the generator. Sound levels at other points around generator may be higher depending on installation. 15-year warranty is an included option for quick ship 80- to 150-kW models.

KOHLER_® GENERATORS TRUSTED WORLDWIDE FOR A CENTURY

We built our first generator in 1920. Today, homes, businesses, hospitals, nuclear power plants – even the National Weather Service – trust in hard-working, long-lasting KOHLER generators.



1925





1946 1960

27

